

# DocuCentre-IV 3065 / 3060 / 2060 Digital Black and White Multifunction Device Productivity, flexibility and simplicity



# Specifications of DocuCentre-IV 3065 / 3060 / 2060 Series

**Copy Function** 

| copy i unction          |   |                                 |                                |
|-------------------------|---|---------------------------------|--------------------------------|
|                         | DocuCentre-IV 3065  | DocuCentre-IV 3060              | DocuCentre-IV 2060             |
| Туре                    | Console type  |                                 |                                |
| Memory                  | System Memory: 1 GB / Page Memory: 512 MB                                       |                                 |                                |
| HDD                     | 160 GB (Usable Space: 40 GB)  |                                 |                                |
| Scanning Resolution     | 600 x 600 dpi   |                                 |                                |
| Warm-up Time            | DC model: 14 sec or less / CP & CF model: 23 sec or less                        |                                 |                                |
| Original Paper Size     | Max: 297 x 432 mm (A3, 11 x 17") for both sheet and book originals              |                                 |                                |
| Output Paper Size       | Max: A3 (297 x 420mm), 11×17" (279 x 431.8mm), Non-standard size: 297 x 431.8mm |                                 |                                |
|                         | Min: A5 (148 x 210mm), Nor  | n-standard size: 139.7 x 182    | mm, Bypass Tray: 88.9 x 98.4mm |
| Output Paper Weight 1   | Tray 1: 60 - 105 gsm, Tr  | <b>ays 2 - 4:</b> 60 - 215 gsm, | Bypass Tray: 60 - 215 gsm      |
| First Copy Output Time  | 35ppm: 4 sec or less 30/25ppm: 4.2 sec or less                                  |                                 |                                |
| Continuous Copy Speed   | 35 ppm  | 30 ppm                          | 25 ppm                         |
| (In Simplex and Duplex) |   |                                 |                                |
| Paper Tray Capacity     | Standard: Tray 1 & 2: 500 sheets, Bypass Tray: 50 sheets                        |                                 |                                |
|                         | Optional: Two Tray Module (Tray 3 & 4): 500 sheets, Tandem Tray Module:         |                                 |                                |
|                         | 900 sheets + 1,100 sheets, HCF B1: 2,000 sheets                                 |                                 |                                |
|                         | Maximum: 4,050 sheets (with Two Tray Module and High Capacity Feeder B1) or     |                                 |                                |
|                         | 5,050 sheets (with Tandem Tray Module and High Capacity Feeder B1)              |                                 |                                |
| Output Tray Capacity    | 500 sheets  |                                 |                                |
| Power Supply            | AC 220 - 240 V, 8 A, 50   | 0/60 Hz                         |                                |
| Power Consumption       | Maximum power consumption: 1,920W (240V AC)                                     |                                 |                                |
|                         | Sleep mode: 2W (240V  | AC)                             |                                |
| Dimensions              | W 596 x D 640 x H 1,1   | 14.5 mm                         |                                |
| Machine Weight          | 65.1 kg   |                                 |                                |
| 1                       |   |                                 |                                |

Performance may vary for heavyweight, coated and special stocks.

### **Print Function**

| -                       | B 41   |                                   |                            |
|-------------------------|--|-----------------------------------|----------------------------|
| Туре                    | Built-in type  |                                   |                            |
| Continuous Print Speed  | 35 ppm   | 30 ppm                            | 25 ppm                     |
| (In Simplex and Duplex) |  |                                   |                            |
| Print Resolution        | Standard: 600 x 60   | 00 dpi (Default) / <b>High Re</b> | solution: 1,200 x 1,200 dp |
| PDL                     | Standard PCL6, PCL5, Optional Adobe® PostScript® 3TM   |                                   |                            |
| Operating System        | Standard: Windows® 2000, Windows® XP, Windows Server® 2003/2008, Windows Vista®, Windows® 7,   |                                   |                            |
|                         | Windows® XP x64, Windows Server® 2003/2008 x64, Windows Vista® x64, Windows® 7 x64, Windows    |                                   |                            |
|                         | Server® 2008 R2 x64, Mac OS X 10.5/10.6  |                                   |                            |
|                         | Optional: Windows® 2000, Windows® XP, Windows Server® 2003/2008, Windows Vista®, Windows® 7,   |                                   |                            |
|                         | Windows® XP x64, Windows Server® 2003/2008 x64, Windows Vista® x64, Windows® 7 x64, Windows    |                                   |                            |
|                         | Server® 2008 R2 x64, Mac OS 9.2.2, Mac OS x 10.3.9 10.4.11 (except 10.4.7), Mac OS X 10.5/10.6 |                                   |                            |
| Connectivity            | Standard: Ethernet   | 100BASE-TX/10BASE-T, US           | B2.0                       |
|                         | Optional: 1000BASI   | E-T                               |                            |

| Scan Function (Optional) |   |  |
|--------------------------|---|--|
| Туре                     | Colour Scanner  |  |
| Scanning Speed           | 55 ppm  |  |
| Scanning Resolution      | 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi  |  |
| Connectivity             | Standard: Ethernet 100BASE-TX/10BASE-T                      |  |
|                          | Optional: Ethernet 1000BASE-T                               |  |
| Scan Destinations        | Scan to Folder, Scan to PC/Server (using FTP/SMB protocol), |  |
|                          | Scan to E-mail , Scan to USB                                |  |

## Fax Function (Optional)

| Send Document Size | Max: A3, 11 x 17", Long documents (Max: 600 mm) |
|--------------------|---|
| Transmission Time  | Less than 3 seconds                             |
| Transmission Mode  | G3  |
| No. of Fax Lines   | PBX, PSTN, Maximum 3 ports                      |

### **Duplex Automatic Document Feeder**

| Capacity            | 110 sheets                            |
|---------------------|---------------------------------------|
| Original Paper Size | Max: A3, 11 x 17", Min: A5            |
| Output Paper Weight | 38 - 128 gsm (In Duplex: 50 - 128gsm) |
| Feeding Speed       | BW: 55 ipm, Colour: 55 ipm            |
| (A4 LEF Simplex)    |                                       |

### Finisher-A1 (Optional)

| Paper Size / Paper Weight | Output Tray: A3, 11 x 17", Min: Postcards (100x148mm), 55 - 220g/m2         |
|---------------------------|---|
| Stacker Capacity          | [Without Staples] A4: 500 Sheets, B4: 250 Sheets, A3 or larger: 200 Sheets, |
|                           | Mixed Size Stacking: 250 Sheets [With Staples] 30 Sets                      |
| Staple                    |   |
| Capacity                  | A4: 50 Sheets (Max 90gsm), B4 or larger: 30 Sheets (Max 90gsm)              |
| Paper Size                | Max: A3, 11 x 17", Min: B5 LEF  |
| Position                  | Single (Front/Angled Staple)  |

### Finisher-B1 (Optional)

|                           | ·   |
|---------------------------|---|
| Paper Size / Paper Weight | Max: A3, 11 x17", Min: B5, 55 - 220gsm  |
| Stacker Capacity          | [Without Staple] A4: 2,000 Sheets, B4: 1,000 Sheets,                          |
|                           | Mixed Size Stacking: 300 Sheets, [With Staples] A4: 100 Sets or 1,000         |
|                           | Sheets, B4 or larger: 75 Sets or 750 Sheets Booklet/Fold: 50 Sets or          |
|                           | 600 Sheets, Fold: 500 Sheets  |
| Staple                    |   |
| Capacity                  | 50 Sheets (Max 90gsm)   |
| Paper Size                | Max: A3, 11 x 17" Min: B5 LEF   |
| Position                  | Single (Front/Angled Back/Straight), Dual (Parallel)                          |
| Punch                     |   |
| Paper Size                | A3,11 x 17", B4, A4, A4LEF, Letter (8.5 x 11"), Letter (8.5 x 11") LEF, B5LEF |
| Number of Holes           | 2 / 4 holes or US 2 / 3 holes   |
| Paper Weight              | 55 to 200 gsm   |
| Booklet Finishing         |   |
| Capacity                  | Booklet: 15 sheets, Fold: 5 sheets  |
| Paper Size                | Max: A3, 11 x 17", Min: A4, Letter (8.5 x 11")                                |
| Paper Weight              | Saddle-Stapling: 64 - 80gsm, Half-Folding: 64 - 105gsm                        |
|                           |   |

# A4 High Capacity Feeder (HCF-B1) Optional

| A4 mgn capacity reeder (nor -b 1) optional |  |  |
|--|--|--|
| Paper Size / Paper Weight                  | A4 LEF, Letter (8.5 x 11") LEF, B5 LEF, 60 - 216 gsm |  |
| Capacity                                   | 2.000 sheets (80gsm)                                 |  |









Descriptions in this material, product specifications and / or appearances are subject to change without prior notice due to improvements. Please note that the product colour appears differently from the actual colour as a result of properties of papers or printing ink. Windows and Windows NT are registered trademarks of Microsoft Corporation. NetWare is a registered trademark of Novell, Inc. in the United States. Macintosh, Mac OS and Ether Talk are trademarks of Apple Computer, Inc. PostScript is a registered trademark of Adobe Systems Incorporated in each country. HP-GL is a registered trademark of Hewlett-Packard Company. Other company names or product names are registered trademarks or trademarks of each company.

Spares for the standard configuration of installed machines is supported for up to 7 years from the date of the end of machine production.

Reproduction Prohibitions Please note that reproduction of the following is prohibited by law:

Domestic and overseas bank notes and coins, government-issued securities, national bonds and local bond certificates.

Unused postage stamps and post cards. Certificate stamps stipulated by law. The reproduction of works for copyright purposes (literary works, musical works, paintings, engravings, maps, cinematographic works, photographic works, etc.) is prohibited except when they are reproduced personally, at home or within limited range according to the above. This product is equipped with an anti-counterfeit feature. This feature is not intended to prevent illegal reproduction. Be extremely careful about the management of equipment used.



XEROX, and the sohere of connectivity design are trademarks or registered trademarks of Xerox Corporation, in the U.S. and/or other countries. DocuCentre is a trademark or registered trademark of Fuji Xerox Co., Ltd.

### For Your Safe Use

Before using the product, read the Instruction Manual carefully for proper use. Use the product with an appropriate adequate power source and voltage displayed. Be sure to establish a ground. In the case of a failure or short circuit, an electric shock may result.

For more information or detailed product specifications, call or visit us at

Fuji Xerox Australia 101 Waterloo Road,

Macquarie Park NSW 2113 Tel. (02) 9856 5000 Fax. (02) 9856 5003

12 17 12

13 14 12



Other trademarks are the property of their respective owners