

ApeosPort-IV

C5575

C4475

C3375

C3373

C2275

FUJI xerox



ApeosPort-IV C5575 / C4475 / C3375 / C3373 / C2275

Digital Colour Multifunction Device

A new way to work effectively



Specifications of ApeosPort-IV C5575 / C4475 / C3375 / C3373 / C2275 Series

Copy Function

	AP-IV C5575	AP-IV C4475	AP-IV C3375	AP-IV C3373	AP-IV C2275
Memory	2GB				
HDD	160 GB (Usable Space: 128 GB)				
Colour Capability	Full Colour				
Scanning Resolution	600 x 600 dpi				
Printing Resolution	1,200 x 2,400 dpi (Multi-value-photo), 600 x 600 dpi (Text / Text-Photo / Photo / Map)				
Warm-up Time	28 sec or less (at room temperature 20°C)				
Original Paper Size	Max. 297 x 432 mm (A3, 11 x 17") for both sheet original and book original				
Output Paper Size	Max. SPAP3 (320 x 450mm) 126 x 177 (320 x 449.6 mm), 12 x 18" (304.8 x 457.2 mm) [For Bypass Tray, Max 320 x 482.6 mm] Min. A5 [For Bypass Tray, Postcard (100 x 148 mm), Envelope (120 x 235 mm)] Image loss: Within 4 mm for lead edge, Within 2 mm for trail edge, Within 2 mm for left / right side				
Output Paper Weight ¹	Tray: 60 - 256 gsm Bypass Tray: 55 - 280 gsm				
First Copy Output Time	3.7 sec <BW> 4.4 sec <BW> 4.9 sec <BW> 4.9 sec <BW> 6.6 sec <BW> 5.2 sec <Colour> 5.7 sec <Colour> 6.4 sec <Colour> 6.4 sec <Colour> 8.7 sec <Colour>				
Continuous Copy Speed	55 ppm <BW> 45 ppm <BW> 35 ppm <BW> 30 ppm <BW> 25 ppm <BW> 50 ppm <Colour> 45 ppm <Colour> 35 ppm <Colour> 30 ppm <Colour> 25 ppm <Colour> A3: 27 ppm <BW> 22 ppm <BW> 20 ppm <BW> 17 ppm <BW> 14 ppm <BW> 25 ppm <Colour> 22 ppm <Colour> 20 ppm <Colour> 17 ppm <Colour> 14 ppm <Colour>				
Paper Tray Capacity	Standard: 2,090 sheets: 500 sheets x 4 Tray + Bypass 90 sheets Optional: HCF B1: 2,030 sheets Tandem Tray Module: 2,500 sheets (Available only for English MFD) Max: 5,120 sheets: 500 sheets + Tandem Tray 2,500 sheets (500 + 867 + 1,133 sheets) + HCF B1 2,030 sheets + Bypass 90 sheets 4,120 sheets: 500 sheets x 4 Tray + HCF B1 2,030 sheets + Bypass 90 sheets				
Output Tray Capacity	Exit 2 Tray: 250 sheets (A4 LEF), Lower Center Tray: 250 sheets (A4 LEF)				
Power Supply	AC 220 - 240 V, 8 A, 50/60 Hz				
Power Consumption	Max: 2.4 kW, Standby: 60 W, Low Power Mode: 42 W, Sleep Mode: 2.2 W				
Dimensions / Weight	From W 640 x D 685 x H 1,28 mm, From 133 kg				

¹ Performance may vary for heavyweight, coated and special stocks.

Print Function

	AP-IV C5575	AP-IV C4475	AP-IV C3375	AP-IV C3373	AP-IV C2275
Print Resolution	Output Resolution: 1,200 x 2,400 dpi, 1,200 x 1,200 dpi Data Process Resolution: Standard: 600 x 600 dpi, High Resolution: 600 x 600 dpi, High Fine: 1,200 x 1,200 dpi				
PDL	PCL6, PCL5, Adobe® PostScript® 3 rd				
Operating System	Microsoft® Windows® 2000, Microsoft® Windows® XP, Microsoft® Windows Server® 2003, Microsoft® Windows Vista®, Microsoft® Windows Server® 2008, Microsoft® Windows® 7, Microsoft® Windows® XP x64, Microsoft® Windows Server® 2003 x64, Microsoft® Windows Vista® x64, Microsoft® Windows Server® 2008 x64, Microsoft® Windows Server® 2008 R2, Microsoft® Windows® 7 x64, Mac OS X 9.2.2, Mac OS X 10.3.9 ~ 10.4.6/10.4.8 ~ 10.4.11/10.5 ~ 10.7				
Connectivity	Standard: Ethernet 100BASE-TX / 10BASE-T, USB2.0 ² Optional: Ethernet 1000BASE-T Bidirectional Parallel (IEEE1284 - B ³)				

Scan Function

	AP-IV C5575	AP-IV C4475	AP-IV C3375	AP-IV C3373	AP-IV C2275
Type	Colour Scanner				
Scanning Resolution	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi				
Scanning Speed	BW: 70 ipm, Color: 70 ipm (DADF) BW: 80 ipm, Color: 80 ipm (Single Pass DADF, Simplex) BW: 140 ipm, Color: 140 ipm (Single Pass DADF, Duplex)				
Connectivity	Standard: Ethernet 100BASE-TX / 10BASE-T Optional: Ethernet 1000 BASE-T				

Fax Function (Optional)

	AP-IV C5575	AP-IV C4475	AP-IV C3375	AP-IV C3373	AP-IV C2275
Send Document Size	Max: A3, 11 x 17", Long document (Max. 600 mm)				
Transmission Time	Less than 3 seconds				
Transmission Mode	G3				
Applicable Lines	Telephone Subscriber Line PBX, PSTN, Max. 3 ports				

Duplex Automatic Document Feeder²

	AP-IV C3375	AP-IV C3373	AP-IV C2275
Original Paper Size	Max: A3, 11 x 17", Min: A5 38 - 128 gsm (In Duplex: 50 - 128 gsm)		
Capacity	110 sheets		
Feeding Speed (A4LEF)	BW: 35 DPM BW: 35 DPM BW: 35 DPM Color: 35 DPM Color: 35 DPM Color: 35 DPM		

² Available on AP-IV C3375/C3373/C2275 models only.

Descriptions in this material, product specifications and / or appearances are subject to change without prior notice due to improvements. Please note that the product colour appears differently from the actual colour as a result of properties of papers or printing ink. Windows and Windows NT are registered trademarks of Microsoft Corporation. NetWare is a registered trademark of Novell, Inc. in the United States. Macintosh, Mac OS and Ether Talk are trademarks of Apple Computer, Inc. PostScript is a registered trademark of Adobe Systems Incorporated in each country. HP-GL is a registered trademark of Hewlett-Packard Company. Other company names or product names are registered trademarks or trademarks of each company.

Spares for the standard configuration of installed machines is supported for up to 7 years from the date of the end of machine production.

For more information or detailed product specifications, call or visit us at

Fuji Xerox Australia 101 Waterloo Road,
Macquarie Park NSW 2113
Tel. (02) 9856 5000 Fax. (02) 9856 5003

13 14 12

<http://www.fujixerox.com.au>

Duplex Automatic Document Feeder³

	AP-IV C5575	AP-IV C4475
Type	Single Pass Duplex Automatic Document Feeder	
Original Paper Size	Max: A3, 11 x 17", Min: A5 38 - 128 gsm (In Duplex: 50 - 128 gsm)	
Capacity	130 sheets	
Feeding Speed (A4LEF)	BW: 55 DPM BW: 45 DPM BW: 35 DPM BW: 35 DPM BW: 35 DPM	
Dimensions / Weight	W 560 x D 498 x H 140 mm, 11 kg	

³ Standard for AP-IV C5575/C4475 models only.

Finisher-A1 (Optional)⁴

	AP-IV C3375	AP-IV C3373	AP-IV C2275
Type	Sorting (Offset available) / Stacking (Offset available)		
Paper Size / Paper Weight	Max: A3, 11 x 17", Min: Postcards (100 x 148 mm), 55 - 220 g/m ²		
Stacker Capacity	[Without Staples] A4: 500 Sheets, B4: 250 Sheets, A3 or larger: 200 Sheets, Mixed Size Stacking: 300 Sheets [With Staples] A4: 100 Sets or 1,000 Sheets, B4 or larger: 75 Sets or 750 Sheets Booklet / Fold ¹ : 50 Sets or 600 Sheets, Fold ² : 500 Sheets		
Staple			
Capacity	A4: 50 Sheets (Max 90 gsm), B4 or larger: 30 Sheets (Max 90 gsm)		
Size	Max: A3, 11 x 17", Min: B5LEF		
Position	Single (Front / Angled Staple)		

⁴ The Optional Finisher-A1 cannot be installed on ApeosPort-IV C5575/C4475.

Finisher-B1 (Optional)

	AP-IV C5575	AP-IV C4475	AP-IV C3375	AP-IV C3373	AP-IV C2275
Type					
Finisher Tray	Sorting (Offset available) / Stacking (Offset available)				
Paper Size / Paper Weight	Max: A3, 11 x 17", Min: B5, 55 - 220 gsm				
Stacker Capacity	[Without Staples] A4: 2000 Sheets, B4: 1,000 Sheets, Mixed Size Stacking: 300 Sheets [With Staples] A4: 100 Sets or 1,000 Sheets, B4 or larger: 75 Sets or 750 Sheets Booklet / Fold ¹ : 50 Sets or 600 Sheets, Fold ² : 500 Sheets				
Staple					
Capacity	50 Sheets (Max 90 gsm)				
Paper Size	Max: A3, 11 x 17", Min: B5LEF				
Position	Single (Front / Angled, Back / Straight), Dual (Parallel)				
Punch					
Paper Size	A3, 11 x 17", B4, A4, A4 LEF, Letter 8.5 x 11", Letter 8.5 x 11" LEF, B5 LEF				
Number of Holes	2 Holes / 4 Holes, or US 2 / 3 Holes				
Paper Weight	55 - 200 gsm				
Booklet Finishing ⁵					
Capacity	Booklet: 15 sheets, Fold: 5 sheets				
Paper Size	Max: A3, 11 x 17", Min: A4, Letter (8.5 x 11")				
Paper Weight	Saddle-Stapling: 64 - 80 gsm, Half-Folding: 64 - 105 gsm				
Dimensions / Weight	W 620 x D 552 x H 987 mm, 28 kg (w/o Booklet Finisher) W 575 x D 597 x H 1057 mm, 37 kg (w/ Booklet Finisher)				

⁵ The optional Finisher B1 Booklet unit is required.

Booklet Finisher-C1 (Optional)

	AP-IV C5575	AP-IV C4475	AP-IV C3375	AP-IV C3373	AP-IV C2275
Staple					
Capacity	50 Sheets (Max 90 gsm)				
Paper Size	Max: A3, 11 x 17", Min: B5				
Position	Single (Front / Back / Angled), Dual (Parallel)				
Punch					
Paper Size	A3, 11 x 17", B4, A4, A4 LEF, Letter (8.5 x 11") LEF, B5 LEF				
Number of Holes	2 / 4 holes (Option US 2 / 3 holes)				
Paper Weight	55 - 200 gsm				
Booklet Finishing					
Capacity	Saddle-Stapling: 15 Sheets, Half-Folding: 5 Sheets, Bi-Fold: 1 Sheet				
Paper Size	Max: SRA3 (320 x 450 mm), 12 x 18" (304.8 x 457.2 mm), Min: A4, Letter (8.5 x 11")				
Paper Weight	Saddle-Stapling: 64 - 90 gsm, Half-Folding: 64 - 105 gsm, Bi-Fold: 64 - 220 gsm				

High Capacity Feeder (Optional)

	AP-IV C5575	AP-IV C4475	AP-IV C3375	AP-IV C3373	AP-IV C2275
Paper Size	A4 LEF, 8.5 x 11" LEF, B5 LEF				
Paper Weight	55 - 216 gsm				
Capacity	2,030 sheets (80 gsm)				

Customer Expectation Document (CED)

For detailed product specifications, optimum performance parameters and service clearances refer to the Customer Expectation Document.

For Your Safe Use

Before using the product, read the Instruction Manual carefully for proper use.

Use the product with an appropriate adequate power source and voltage displayed. Be sure to establish a ground.

In the case of a failure or short circuit, an electric shock may result.



FUJI XEROX