

DocuCentre-V
C7775 / C6675 / C5575 / C4475 / C3375 / C3373 / C2275



DocuCentre-V

C7775 / C6675 / C5575 / C4475 / C3375 / C3373 / C2275
Digital Colour Multifunction Device

A new standard in flexibility and efficiency to allow
you to work smarter

FUJI xerox

Specifications of DocuCentre-V C7775 / C6675 / C5575 / C4475 / C3375 / C3373 / C2275

Basic Specifications/Copy Function

Item	DocuCentreV C7775	DocuCentreV C6675	DocuCentreV C5575	DocuCentreV C4475	DocuCentreV C3375	DocuCentreV C3373	DocuCentreV C2275
Memory Capacity	4 GB						
Hard Disk Capacity	160 GB or larger (Usable space: 128 GB)						
Scanning Resolution	600 x 600 dpi						
Printing Resolution	1,200 x 2,400 dpi (High Resolution Photo), 600 x 600 dpi (Text/Text-Photo/Photo/Map)						
Warm-up Time	30 seconds or less (20 degrees Celsius room temperature). 24 seconds or less if the main power is on (20 degrees Celsius room temperature)						
Original Paper Size	Maximum of 297 x 432 mm (A3, 11 x 17") for both Sheet and Book						
Paper Size	Max	SRA3 (320 x 450 mm), 12.6 x 17.7" (320 x 449.6 mm), 12 x 18" (304.8 x 457.2 mm), A3 [12 x 19" (304.8 x 482.6 mm) when using Bypass Tray]					
	Min	A5 [Postcard and Quadrat NO.3 Envelope (120 x 235 mm) when using Bypass Tray]					
	Image loss width	Lead edge 4 mm or less, trail edge 2 mm or less, and right&left 2 mm or less					
Paper Weight*1	Paper Tray	52 - 300 gsm					
	Bypass Tray	52 - 300 gsm					
First Copy Output Time*2	B/W: 3.3 sec. Colour: 4.1 sec.	B/W: 3.3 sec. Colour: 4.1 sec.	B/W: 3.7 sec. Colour: 5.2 sec.	B/W: 4.4 sec. Colour: 5.7 sec.	B/W: 4.9 sec. Colour: 6.7 sec.	B/W: 4.9 sec. Colour: 6.4 sec.	B/W: 6.6 sec. Colour: 8.7 sec.
Continuous Copy Speed*3	A4	B/W: 70 ppm Colour: 70 ppm	B/W: 65 ppm Colour: 65 ppm	B/W: 55 ppm Colour: 50 ppm	B/W: 45 ppm Colour: 45 ppm	B/W: 35 ppm Colour: 35 ppm	B/W: 30 ppm Colour: 30 ppm
	A3	B/W: 35 ppm Colour: 35 ppm	B/W: 32 ppm Colour: 32 ppm	B/W: 27 ppm Colour: 25 ppm	B/W: 22 ppm Colour: 22 ppm	B/W: 20 ppm Colour: 20 ppm	B/W: 17 ppm Colour: 17 ppm
Paper Tray Capacity*4	Standard	[C7775/C6675/C5575/C4475/C3375/C2275] 500 sheets x 2 Tray + 867 sheets + 1,133 sheets + Bypass Tray 90 sheets [C5575/C4475/C3375/C3373/C2275] 4 Tray Model: 500 sheets x 4 Tray + Bypass Tray 90 sheets					
	Optional	HCF B1: 2,030 sheets					
Maximum Paper Capacity	[C7775/C6675/C5575/C4475/C3375/C3373/C2275] 5,120 sheets (Tandem Tray Model + High Capacity Feeder B1) [C5575/C4475/C3375/C3373/C2275] 4,120 sheets (4 Tray Model + High Capacity Feeder B1)						
		250 sheets (A4 LEF), 125 sheets (A3)					
Output Tray Capacity*4*5							
Power Source	AC 220 - 240 V, 8 A, 50/60 Hz						
Power Consumption	2.4kW or less Sleep mode: 1.3W or less Standby mode: 119W or less	2.4kW or less Sleep mode: 1.3W or less Standby mode: 105W or less	2.4kW or less Sleep mode: 1.3W or less Standby mode: 56W or less				
Dimensions	[C7775/C6675/C5575/C4475/C3375/C3373/C2275] W 640 x D 699 x H 1,143 mm (when Duplex Automatic Document Feeder B1-PC is installed) [C3375/C3373/C2275] W 640 x D 699 x H 1,128 mm (when Duplex Automatic Document Feeder B1-C is installed)						
Weight*6	148 kg (With Fax and Duplex Automatic Document Feeder B1-PC)	135 kg*7 (With Fax and Duplex Automatic Document Feeder B1-PC)	130 kg*7 (With Fax and Duplex Automatic Document Feeder B1-C)				

*1: Fuji Xerox advises that operators use its recommended paper. Performance may vary for supported speciality and heavy weight media. Documents may not be printed correctly depending on usage conditions. *2: B/W: A4 LEF/ Monochrome priority mode, Colour: A4 LEF/Colour priority mode *3: The speed may be reduced due to the image quality adjustment. *4: 80gsm Paper. *5: When the Inner Output Tray is installed, the center tray capacity is 250 sheets (A4 LEF) and the Inner Output Tray capacity is 250 sheets (A4 LEF). *6: Excluding Toner Cartridge. *7: With the 3 Tray Module.

Print Function

Item	Description						
Printing Resolution	1,200 x 2,400 dpi						
PDL	Standard PCL5/PCL6 Optional Adobe® PostScript® 3™						
Supported Operating System*1	[PCL6] Windows® XP, Windows Server® 2003 (32-bit) Windows® Vista® (32-bit), Windows Server® 2008 (32-bit) Windows® 7 (32-bit), Windows® 8 (32-bit) Windows® XP Professional (64-bit), Windows Server® 2003 (64-bit) Windows® Vista® (64-bit), Windows Server® 2008 (64-bit) Windows® 7 (64-bit), Windows Server® 2008 R2 (64-bit) Windows® 8 (64-bit), Windows Server® 2012 (64-bit) [Mac OS X Driver] Mac OS X 10.5/10.6/10.7/10.8						
Interface	Standard Ethernet 100BASE-TX/10BASE-T, USB2.0 Optional Ethernet 1000BASE-T, Bidirectional Parallel (IEEE1284-B)						

*1: See our official website for the latest supported OS.

Scan Function

Item	DocuCentreV C7775	DocuCentreV C6675	DocuCentreV C5575	DocuCentreV C4475	DocuCentreV C3375	DocuCentreV C3373	DocuCentreV C2275
Type	Colour Scanner						
Scanning Resolution	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi						
Original Scanning Speed*1	Duplex Automatic Document Feeder B1-C	—					B/W: 70 ppm, Colour: 70 ppm
Duplex Automatic Document Feeder B1-PC	B/W: 80 ppm Colour: 80 ppm 1 pass, 2 sided scanning B/W: 160 ppm Colour: 160 ppm	B/W: 80 ppm Colour: 80 ppm 1 pass, 2 sided scanning B/W: 150 ppm*2 Colour: 150 ppm*2					
Interface	Standard Ethernet 100BASE-TX/10BASE-T Optional Ethernet 1000BASE-T						

*1: The scanning speed varies depending on the documents. *2: 160 ppm for both B/W and colour when Quiet Mode is disabled. For DocuCentre-V C6675/C5575/C4475/C3375/C3373/C2275, Quiet Mode is enabled by factory default. This setting can be changed to suit the customer's usage.

Fax Function (Optional)

Item	Description		
Document Size	Max: A3, 11 x 17", Long document (Longest 600 mm)		
Recording Paper Size	Max: A3, 11 x 17" Min: A5		
Transmission Time	2 seconds and more but fewer than 3 seconds		
Transmission Mode	ITU-T G3		
Applicable Lines	Telephone subscriber line, PBX, fax communication (PSTN), maximum 3 ports (G3-3 port)		

HCF B1 (Optional)

Item	Description
Paper Size / Paper Weight	A4 LEF, Letter LEF, B5 LEF, 55 - 216 gsm
Feeding Capacity*1 / Number of Tray	2,030 sheets x 1-tray
Dimensions / Weight	W 389 x D 610 x H 380mm, 29 kg

*1: 80gsm paper.

Customer Expectation Document (CED)

For detailed product specifications, optimum performance parameters and service clearances refer to the Customer Expectation Document.

Standard Duplex Automatic Document Feeder B1-C

Item	DocuCentre-V C3375	DocuCentre-V C3373	DocuCentre-V C2275
Original Size / Paper Weight	Max: A3, 11 x 17"; Min: A5*1 38 - 128 gsm (In Duplex: 50 - 128 gsm)		
Capacity*2	110 sheets		
Feeding Speed (A4 LEF Simplex)	B/W: 35 ppm Colour: 35 ppm	B/W: 30 ppm Colour: 30 ppm	B/W: 25 ppm Colour: 25 ppm
Dimensions / Weight	W 560 x D 498 x H 125 mm, 8 kg		

*1: Nonstandard size single-sided mode: 125 x 85mm. *2: 64 gsm paper.

Single-Pass Duplex Automatic Document Feeder B1-PC (Optional)

Item	DocuCentre-V C7775	DocuCentre-V C6675	DocuCentre-V C5575	DocuCentre-V C4475	DocuCentre-V C3375	DocuCentre-V C3373	DocuCentre-V C2275
Original Size / Paper Weight	Max: A3, 11 x 17"; Min: A5*1 38 - 128 gsm (In Duplex: 50 - 128 gsm)						
Capacity*2	130 sheets						
Feeding Speed (A4 LEF Simplex)	B/W: 70 ppm Colour: 70 ppm	B/W: 65 ppm Colour: 65 ppm	B/W: 55 ppm Colour: 50 ppm	B/W: 45 ppm Colour: 45 ppm	B/W: 35 ppm Colour: 35 ppm	B/W: 30 ppm Colour: 30 ppm	B/W: 25 ppm Colour: 25 ppm
Dimensions / Weight	W 560 x D 498 x H 140mm, 11 kg						

*1: Nonstandard size single-sided mode: 125 x 85mm. *2: 64 gsm paper.

Finisher-A1 (Optional)

Item	Description	
Type	Sort (Offset available) / Stack (Offset available)	
Paper Size	Max: A3, 11 x 17"; Min: Postcard	
Paper Weight	52 - 220 gsm	
Paper Capacity	Finishing Tray [Without Stapling] A4: 500 sheets; B4: 250 sheets; A3 or larger: 200 sheets; Mixed Size Stacking: 250 sheets [With Stapling] 30 copies	
Staple	Capacity A4: 50 sheets (90 gsm or less), B4 or larger: 30 sheets (90 gsm or less) Paper Size Max: A3, 11 x 17"; Min: B5 LEF Position Single stapling (Front/Angled)	
Dimensions / Weight	W 559 x D 448 x H 246mm, 12 kg	

Note: The unit cannot be installed on DocuCentre-V C7775/C6675/C5575/C4475.

Finisher-B1 (Optional)

Item	Description	
Type	Sort (Offset available) / Stack (Offset available)	
Paper Size*1	Max: A3, 11 x 17"; Min: B5 LEF	
Paper Weight	52-220 gsm	
Paper Capacity	[Without Stapling] A4: 2,000 sheets; B4 or larger: 1,000 sheets; Mixed Size Stacking: 300 sheets [With Stapling] A4: 100 copies or 1,000 sheets, B4 or larger: 75 copies or 750 sheets [With Booklet Finishing]*2 50 copies or 600 sheets [With Scoring] 500 sheets	
Staple	Capacity 50 sheets (90 gsm or less) Paper Size Max: A3, 11 x 17"; Min: B5 LEF Position Single stapling (Front/Angled, Back/Straight) or dual stapling (Parallel)	
Punch*3	Number of Holes 2-hole/4-hole punch or 2-hole/3-hole punch (US Specifications) Paper Size A3, 11 x 17", B4, A4, A4 LEF, Letter, Letter LEF, B5 LEF Paper Weight 55 - 200 gsm	
Booklet Finishing*2	Capacity Saddle Staple: 15 sheets; Scoring: 5 sheets Paper Size Max: A3, 11 x 17"; Min: A4, Letter Paper Weight Saddle Staple: 64 - 80 gsm, Scoring: 64 - 105 gsm	
Dimensions / Weight	W 620 x D 552 x H 987mm, 28 kg With Booklet Finisher: W 620 x D 597 x H 1,057 mm, 37 kg	

*1: Paper in the sizes larger than A3 or 11 x 17" or smaller than B5 are delivered to the Center Tray. *2: The Booklet Finishing function requires the Booklet Maker Unit for Finisher-B1. *3: The Punch function requires the 2/4 Hole Punch Kit for Finisher-B1 or US 2/3 Hole Punch Kit for Finisher-B1. Note: The unit cannot be installed on DocuCentre-V C7775/C6675.

Descriptions in this material, product specifications and / or appearances are subject to change without prior notice due to improvements. Please note that the product colour appears differently from the actual colour as a result of properties of papers or printing ink. Windows is registered trademark of Microsoft Corporation. Other company names or product names are registered trademarks or trademarks of each company.

<Reproduction Prohibitions> Please note that reproduction of the following is prohibited by law:
Domestic and overseas bank notes and coins, government-issued securities, national bonds and local bond certificates. Unused postage stamps and post cards. Certificate stamps stipulated by law. The reproduction of copyrighted works (literary works, musical works, paintings, engravings, maps, cinematographic works, photographic works, etc.) is prohibited except when they are reproduced personally, at home or within limited range.

C3 Finisher with Booklet Maker (Optional)

Item	Description	
Type	Output Tray	Sort/Stack
	Finishing Tray	Sort (Offset available) / Stack (Offset available)
	Booklet Tray	Sort/Stack
Paper Size*1	Output Tray	Max: 12 x 19" (304.8 x 482.6 mm); Min: Postcard
	Finishing Tray	Max: 12 x 19" (304.8 x 482.6 mm); Min: B5
	Booklet Tray	Max: 12 x 18" (304.8 x 457.2mm); Min: B5
Paper Weight	Output Tray	52 - 300 gsm
	Finishing Tray	52 - 300 gsm
	Booklet Tray	60 - 105 gsm*3
Paper Capacity	Output Tray	500 sheets (A4)
	Finishing Tray	[Without Stapling] A4: 1,500 sheets; B4 or larger: 1,500 sheets; Mixed Size Stacking 300 sheets [With Stapling] A4: 200 copies or 1,500 sheets; B4 or larger: 100 copies or 1,500 sheets; Mixed Size Stacking: 70 copies or 200 sheets
	Booklet Tray	20 copies
Staple	Capacity	50 sheets (90 gsm or less)*2
	Paper Size	Max: A3, 11 x 17"; Min: B5
	Position	Single stapling (front/back, angled), dual stapling (parallel)
Punch	Number of Holes	2-hole/4-hole punch or 2-hole/3-hole punch
	Paper Size	A3, 11 x 17", B4, A4, A4 LEF, Letter, Letter LEF (8.5 x 11"), B5 LEF, 7.25 x 10.5", 8 x 10", 16K, Cover A4, 9 x 11", 215 x 315 mm, 8.5 x 13", Legal (8.5 x 14"), 11 x 15", 8K
	Paper Weight	52 - 200 gsm
Booklet Finishing	Capacity	Saddle Staple: 16 sheets; Fold: 5 sheets; Single Fold: 1 sheet
	Paper Size	Max: SRA3 (320 x 450 mm), 12 x 18" (304.8 x 457.2 mm); Min: B5
	Paper Weight	Saddle Staple: 60 - 105*4,5 gsm; Middle-Fold: 60 - 105*4,5 gsm; Single Fold: 60 - 105 gsm
Dimensions / Weight	W 790 x D 589 x H 1,056 mm, 61 kg W 1,025 x D 726 x H 1,056 mm, 115 kg (when Folder Unit CD1 and Punch Unit are installed)	

*1: Paper less than B5 size is delivered from the Center Tray. *2: Up to 65 sheets can be stapled when the C3 Finisher Staple Unit 65 Sheets is installed. *3: Cover sheets can be up to 256 gsm. *4: Covers can be up to 256 gsm (Thick Paper 2) for saddle staple during printing. *5: Printed covers can be up to 169 gsm (Thick Paper 1) for middle-fold or saddle staple during copying, while blank covers can be up to 256 gsm (Thick Paper 2).

Folder Unit CD1 (Optional)

Item	Description	
Paper Size	Z Fold Half Sheet	A3, 11 x 17", B4
	Tri-fold	A4, Letter
Paper Weight	Z Fold Half Sheet	60-90 gsm
	Tri-fold	60-90 gsm
Power / Maximum power consumption	AC100V +/- 10%, 1.0A, 50/60Hz common, 100W or less	
Dimensions / Weight	W 232 x D 726 x H 991mm, 52.1 kg or less	

Note: Power supply separate from the main unit is required.

Side Tray

Item	Description	
Paper Size / Paper Weight	Same as the Basic Specifications / Copy Function	
Paper Capacity*1	100 sheets	
Dimensions / Weight	W 353 x D 469 x H 198mm, 1kg	

*1: 64 gsm paper.



<For Your Safe Use>

- Before using the product, read the Instruction Manual carefully for proper use.
- Use the product with an appropriate and adequate power source and voltage displayed.
- Be sure to ground the machine. In the case of a failure or short circuit, an electric shock may result.

For more information or detailed product specification, please call or visit us at

Fuji Xerox Australia

101 Waterloo Road, Macquarie Park NSW 2113

Tel. (02) 9856 5000 Fax. (02) 9856 5003

<http://www.fujixerox.com.au>

